

ALLATION SYSTEM

PIPELINE FIXING VARIANTS

 $\label{thm:constraint} \textbf{UTECHINSTALLATION}\, \textbf{SYSTEMS}\, \textbf{PORTFOLIO}\, \textbf{ALLOWS}\, \textbf{IMPLEMENTING}\, \textbf{SOLUTIONS}\, \textbf{FROM}\, \textbf{THE}\, \textbf{SIMPLEST}\, \textbf{SUPPORTS}\, \textbf{TO}\, \textbf{COMPLEX}\, \textbf{STRUCTURES}.$

Examples of typical supports are shown below. Refer to UTECH technical solutions album for more technical solutions. Please get in touch with a UTECH engineer for such an album.







SINGLE HANGER

MULTIPLE PIPE HANGER

SINGLE PIPE SPREADER BAR







SPREADER BAR FOR MULTIPLE PIPES

FRAME TO THE FLOOR

VERTICAL SECTION FIXING









BRACKET PIPE FIXING

REINFORCED BRACKET PIPE FIXING


BRACKET FIXING OF TWO PIPES

BASIC ELEMENTS










See section

«Connectors»






20

ADVANTAGES

- Unique and comprehensive solution. Assemblies consisting entirely of installation systems for support structures, clamps and clips for pipe fixing, anchors for fixing in concrete, fixing to steel
- Fasteners withstand high loads

- Wide range of applications, from standard hangers to unique solutions
- Engineering services for the design of utility fasteners for the development of individual assemblies or a complete project application and, therefore, correct cost estimation



INSTALLATION SYSTEMS

Profile systems have been successfully tested for seismic loads, aggressive media and fire.

Certified software is used for the calculation of supports, taking into account the norms and standards of the Russian Federation.

Libraries of elements and supports are available for independent use in AutoCAD®, AVEVA, SmartPlant, and Revit® software environments.

COMPLEX SUPPORTS

Design of supports taking into account the mutual alignment of networks. This approach saves resources during installation.

The complex support allows for multiple fixing stages and takes into account the sequence of installation.

If necessary, the networks can be additionally anchored after checking the load-bearing capacity of the assembly.



